

SANYO VCC-HD4600 1080p 4 MEGAPIXEL DAY-NIGHT 10x AF NETWORK CAMERA WITH AUDIO

Sanyo Company
Security Products Division
21605 Plummer Street
Chatsworth, CA 91311
Phone: 888. 818. 2597
Fax: 818.717.2716 223 9180
<http://us.sanyo.com/security>

November, 2009

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, based on Master Format 2004 and The Project Resource Manual—CSI Manual of Practice. The Manufacturer is responsible for technical accuracy. By removing the references to specific Sanyo product names or part numbers, the text may be used also in performance-based specifications.

The section must be carefully reviewed and edited by the Architect or Engineer to meet the requirements of the project and local building code. Words and sentences within brackets [] are choices to include or exclude a particular item or statement. Coordinate this section with other specification sections and the Drawings.

SECTION 28 23 29 **VIDEO SURVEILLANCE REMOTE DEVICES AND SENSORS** **Sanyo VCC-HD4600 4 MEGAPIXEL DAY/NIGHT 10x AF NETWORK CAMERA WITH** **AUDIO**

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes
 - 1. Video Surveillance Remote Devices
- B. Related Sections
 - 1. Section 28 23 13 – Video Surveillance Control and Management Systems
 - 2. Section 28 23 16 – Video Surveillance Monitoring and Supervisory Interfaces
 - 3. Section 28 23 19 – Digital Video Recorders and Analog Recording Devices
 - 4. Section 28 23 23 – Video Surveillance Systems Infrastructure

1.2 REFERENCES

- A. Federal Communications Commission (FCC) (www.fcc.gov)
 - 1. FCC CFR 47 part 15 Class B – Telecommunications – Radio Frequency Devices – Digital Emission
- B. International Electrotechnical Commission (IEC)
 - 1. IEC 60529 Degrees of Protection provided by enclosures (IP Code)

~~2. IEC 60950 Information Technology Equipment – Safety~~

- C. Institute of Electrical and Electronics Engineers, Inc. (IEEE) (www.ieee.org)
 - 1. IEEE 802.3af Power Over Ethernet
- D. International Organization of Standardization (ISO)
 - 1. 9001 – Quality System
- E. Underwriters Laboratories, Inc. (UL) (www.ul.com)
 - ~~1. UL 2043 Fire Test for heat and Visible Smoke Release for Discrete Products and their Accessories Installed in Air Handling Spaces~~
 - UL 2044 Commercial Closed-Circuit Television Equipment

1.3 SYSTEM DESCRIPTION

- A. Video Surveillance Remote Devices
 - 1. 4 Megapixel 1080p Full High Definition Day/Night Network CMOS Camera with Audio.
- B. Performance Requirements
 - 1. Provide surveillance with high definition detail images – day or night.
 - 2. Possesses advanced intelligence features.
 - 3. The camera shall be of manufacturer's official product line, designed for commercial/industrial continuous 24/7 use.
 - 4. The camera shall be based upon standard components and proven technology.

1.4 SUBMITTALS

- A. Submit under provisions of Section [01 33 00.]
- B. Product Data:
 - 1. Manufacturer's data, user and installation manuals for all equipment and software programs including computer equipment and other equipment required for complete video system.
- C. Shop Drawings; include
 - 1. System device locations on architectural floor plans.
 - 2. Full Schematic of system, including wiring information for all devices.
- D. Closeout Submittals
 - 1. User manual.
 - 2. Parts list.
 - 3. System device locations on architectural floor plans.
 - 4. Wiring and connection diagram.
 - 5. Maintenance requirements.

1.5 QUALITY ASSURANCE

- A. Manufacturer:
 - 1. Minimum of 10 years experience in manufacture and design Video Surveillance Devices.
 - 2. Manufacturer's quality system: Registered to ISO 9001 Quality Standard.
- B. Video Surveillance System

~~C. Listed by UL and FCC specifically for the required loads. Provide evidence of compliance upon request.~~

- D. Installer:
1. Minimum of 5 years experience installing Video Surveillance System.
 2. All camera installation, configuration, setup, program and related work shall be performed by electronic technicians thoroughly trained by the manufacturer in the installation and service of the equipment provided.

1.6 DELIVERY, STORAGE AND HANDLING

- A. Comply with requirements of Section [01 60 00]
- B. Deliver materials in manufacturer's original, unopened, undamaged containers; and unharmed original identification labels.
- C. Protect stored materials from environmental and temperature conditions following manufacturer's instructions.
- D. Handle and operate products and systems according to manufacturer's instructions.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer
- Sanyo Company
Security Products Division
21605 Plummer Street
Chatsworth, CA 91311
Phone: 888. 818. 2597
Fax: 818.717.2716
<http://us.sanyo.com/security>
- B. Substitutions: Under provisions of Division 1
1. All proposed substitutions must be approved by the Consultant, or Architect/Engineer professional.
 2. Proposed substitutions must provide a line-by-line compliance documentation.

2.2 4 Megapixel 1080p Full High Definition Day/Night 10x AF Network Camera with Audio

- A. General Characteristics:
1. Be designed to provide advanced image support resolutions up to 4 Megapixels of effective picture elements ~~2320~~ 2288(H) x ~~1728~~ 1712(V).
 2. Provide dual Codec for simultaneous H.264 and JPEG transmission.
 3. Be designed to provide 1080p H.264 compressed video at 30 frames per second.
 4. Use a high quality 1/2.5" CMOS progressive scan image sensor
 5. 10x Optical Zoom Auto Focus 4-Megapixel Rated Lens
 6. Provide color pictures in light down to 2.0 lux at F 1.8
 7. Provide B/W pictures in light down to 0.1 lux at F 1.8

SANYO VCC-HD4600 1080p 4 MEGAPIXEL DAY-NIGHT 10x AF NETWORK CAMERA WITH AUDIO

8. Provide for Audio input and output directly to and from the camera
9. Be capable of accepting power from **12V DC**, 24V AC or IEEE 802.3af Power-over-Ethernet (PoE)
10. Be capable of transmitting analog NTSC video for setup and installation purposes
11. Be capable of storing images on-camera via SDHC storage
- B. Camera shall be capable of the following adjustments and features:
 1. Support the following connections/interfaces
 - a. 2 alarm inputs (NC/NO)
 - b. 2 alarm outputs (NC/NO)
 - c. **12V DC**, 24V AC Power Input
 - d. Ethernet Port (Data and IEEE 802.3af PoE)
 - e. HDMI Output (1080p @ 30 ips)
 - f. Audio Mic In
 - g. Audio Line Out
 - h. USB 2.0 for External HDD (* requires dedicated HDD case)
 - i. SDHC Card Slot
 - j. BNC Analog Output **for setup, 75 ohm, approx.1 volt peak to peak**
 - ~~2. Ensure that any setup or instructional commands required to program the camera, fine tune the camera or adjust any special settings of the camera will be accomplished by using a simple on screen display menu operated by control buttons on the side of the camera.~~
 3. **Provide image stabilization.**
 4. The camera will provide a sixteen (16) character camera ID.
 5. Provide selection of languages from English, French, German, Japanese and Spanish.
 6. Progressive Scan CMOS technology for image clarity.
 7. Four (4) Megapixels maximum resolution
 8. ~~Four~~**Five** levels of operator privileges shall be available.
 - a. Admin level shall have full access to all functions.
 - b. **Operator1 level shall have access to all functions except Network settings.**
 - c. Operator**2** level shall have access to all functions except configuration settings.
 - d. Download level shall be restricted to downloading recorded images only.
 - e. Guest will be restricted to monitoring live video only.
 9. Provide Day & Night function allowing automatic changeover from color mode to B&W mode as well as removal of an IR cut filter during low light operation.
 - ~~10. Automatic mechanical back focus that provides Focus Assist functionality to ensure images are always in focus and to remove the need for IR corrected optics for low light use.~~

11. Camera shall have advanced programmable motion detection. Selectable modes include
 - a. Motion Detection
 - b. Motion Masking
 - c. Off.
 12. Human Face Detection shall be available in both Detection and Masking modes selectable by area.
 - a. Up to 32 faces shall be detectable at once.
 - b. The camera shall tune its focus, ~~BLC gain and other image optimization controls~~ via detected faces
 - c. The camera shall be able to transmit an alarm based on detecting one or more faces ~~and motion detection at the same time~~ in the scene.
 13. The camera shall support digital trip wire functionality at no additional cost
 - a. Up to 8 digital tripwires shall be configurable with independent controls for length, angle, vector (left to right, right to left or both) and tripwire sensitivity.
 - b. ~~Up to 4 areas shall be configurable.~~
 14. The camera shall support Back Light Compensation (BLC) circuitry
 15. Provide HD image recording to an on-board SD memory card slot (card optional)
 16. Provide flexible on-board recording capability allowing recording by Alarm (motion or input 1/2) including programmable pre-alarm recording, or Back-up in the event of loss of network.
 17. Provide internal verification whether or not any electronic alteration was made to original images.
 18. When image data is output on a conventional SD output
The camera shall ~~reduce or~~ eliminate "smearing" associated caused by vertical noise associated with bright spots (such as headlights).
- C. Video Requirements and Adjustments:
1. Minimum Adjustments and Requirements
 - a. Imager: Progressive Scan ~~1/2.5" 4/3"~~ inch CMOS.
 - b. Pixels: ~~2320~~2288(H) x ~~1728~~1712(V) effective picture elements.
 - c. Image Size: H.264 – 16:9 HD: 1920 x 1080~~p~~, 30 ips. ~~H.264~~ HD: 1280 x 720~~p~~ 30 ips; ~~960 x 540p 30 ips~~; 640 x 360~~p~~ 30 ips; 320 x 180~~p~~ 30 ips. H.264 4:3: 1600x1200 30 ips; 1280 x 960~~p~~ 30 ips; 1024 x 768 30 ips; ~~720 x 480p 30 ips~~; 640x480 30 ips; 320 x 240~~p~~ 30 ips.
 - d. Image Size: MJPEG 16:9 HD: 1920 x 1080; HD 1280 x 720; 1024 x 576; 640 x 360. JPEG 4:3 4M: 2288 x 1712, 2M: 1600 x 1200, 1280 x 960; 1024 x 768; 800 x 600; 640 x 480; 320 x 240.

- e. Iris Control: Selectable Auto/Manual. ~~Selectable electronic shutter in manual mode.~~
 - f. Shutter: Electronic range of 1/30, 1/60, 1/100, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/10000. Long shutter: x1, x2, x4, x8, x16, x32.
 - ~~g. Synchronization: Internal synchronization.~~
 - h. Aperture Compensation: Selectable On/Off.
 - i. Minimum Color Illumination: ~~2.04-0~~ lux at F ~~1.84-2~~ Minimum B/W Illumination: 0.1 lux at F ~~1.84-2~~
 - j. Signal to Noise Ratio: more than 50 dB (AGC off).
 - k. The camera shall provide selectable White Balance settings include Auto-tracing White (ATW), AWC for technical support adjustments; Outdoor, Indoor, Fluorescent and Manual control (MWB). MWB allows individual red and blue adjustments.
 - l. The camera shall support Backlight Compensation: Selectable Multi-spot metering, Center-zone metering, Face and Off. Mask settings available.
 - ~~m. Light Control: Optical auto iris lens or Electronic iris.~~
 - n. Auto-focus: Selectable Auto/Manual/One push. Selectable focus area.
 - o. Day/Night: Selectable Auto/Color/Black and White.
 - p. AGC Gain: Selectable Normal/Middle/High/Off. Adjustable gain control in Off mode.
 - q. Gamma: 0.45/1, other settings available.
 - r. Electronic Sensitivity Boost: Selectable Auto/Off. Max. 32x.
- D. Operating Environment:
- 1. PC: IBM PC/AT or compatible.
 - 2. Operating System: Windows XP ~~Professional~~ SP2 or Windows Vista
 - 3. CPU: Core2Duo E~~67008500~~ ~~2.663-16~~ GHz or higher.
 - 4. Memory: Windows XP : 1 GB or more. Windows Vista: 2 GB or higher.
 - 5. Network Interface: 10/100Base-TX (RJ-45 connector).
 - 6. Display Card: 1920 x 1200 pixels or higher.
 - 7. Graphics Chip: ATI Radeon HD2600 series or higher; nVidia GeForce 8600 series or higher; nVidia Quadro FX550 series or higher.
 - 8. Web Browser: Internet Explorer Ver 6.0 SP2 ~~or higher~~, or Ver 7.0
- E. IP Interfaces:
- ~~1. The camera shall use a dedicated video compression chip (CODEC) and be equipped with a minimum of 8MB memory.~~
 - 2. Protocols supported include TCP/IP, HTTP, HTTPS, UDP, SMTP, FTP, DHCP, DDNS, NTP, RTP, RTSP.
 - 3. Camera IP interface at 10 Base-T/100 Base-TX/PoE compatible.
 - 4. The camera shall interface to Microsoft Internet Explorer ~~ver 6.0 SP2 or higher or ver. 7.0 and higher~~ via Plug-in module software

- making video images and configuration menus available ~~in a standard browser environment using HTTP.~~
5. When accessed from a browser on-line, context sensitive help shall be provided.
 6. The camera shall provide an integral E-mail function for up to five (5) E-mail addresses. E-mails can be automatically sent as an alarm notification or at regular intervals. An image can be attached to the e-mail in either case.
 7. Web access protected by user ID and password. A maximum of ~~2046~~ users shall be assignable.
 8. Camera shall maintain a transactional log when accessed via the network containing the most recent 100 times and IP addresses of those given access.
 9. Camera shall maintain an "Up Log" showing power on time; SD Memory record time; External HDD record time and a Camera High Temperature warning.
 10. Up to ~~200~~ users may access a camera via the web server simultaneously.
 11. Two alarm inputs (NO/NC) shall be provided.
 12. Two alarm output (NO/NC) shall be provided.
 13. The camera shall support both fixed IP addresses and dynamically assigned IP addresses provided by a Dynamic Host Control Protocol (DHCP) server.
 14. The camera shall be able to interface with SANYO Video Pilot software. Video Pilot shall support full functionality when operating on Windows Vista or Windows XP Professional Edition with SP2/SP3.
 15. Third party application integration of the camera is supported via two (2) Development Kits which provide the necessary information for interfacing. Contact SANYO for details.
 16. Image quality selectable at Basic, Normal, Enhanced (default), Fine and Super Fine.
 17. Resolutions may be set for Live, Recorded ~~and Transmitted~~ modes.
 18. Recording Time Examples:

CODEC	Resolution	Pic Quality	Recording	Bit Rate	Record Hrs
		16:9	Rate (max)	(approx)	Per 80GB
H.264	1920 x 1080	Enhanced	30 ips	6.0 Mbps	19.2
	1280 x 720	Enhanced	30 ips	4.6 Mbps	25.0
	640 x 360	Enhanced	30 ips	0.98 Mbps	115.6
	1920 x 1080	Basic	30 ips	4.0 Mbps	28.7
	1280 x 720	Basic	30 ips	2.5 Mbps	45.7

SANYO VCC-HD4600 1080p 4 MEGAPIXEL DAY-NIGHT 10x AF NETWORK CAMERA WITH AUDIO

	640 x 360	Basic	30 ips	0.46 Mbps	239.1
MJPEG	1920 x 1080	Enhanced	5 ips	8.96 Mbps	12.9
	1280 x 720	Enhanced	10 ips	9.36 Mbps	12.3
	1024 x 576	Enhanced	15 ips	9.00 Mbps	12.8
	1920 x 1080	Basic	5 ips	3.4 Mbps	21.3
	1280 x 720	Basic	10 ips	4.8 Mbps	24.0
	640 x 360	Basic	30 ips	3.84 Mbps	29.9

* without audio recording

19. Selectable IP resolutions include:

- a. 1920x1080 H.264
- b. 1280x720 H.264
- c. 640x360 H.264
- d. 320x180 H.264~~5~~
- e. 1920x1080 MJPEG
- f. 1280x720 MJPEG
- g. 1024x576 MJPEG
- h. 640x360 MJPEG
- i. 1600x1200 H.264
- j. 1280x960 H.264
- k. 1024x768 H.264
- l. 640x480 H.264
- m. 320x240 H.264
- n. 2288x1712 MJPEG
- o. 1600x1200 MJPEG
- p. 1280x960 MJPEG
- q. 1024x768 MJPEG
- r. 800x600 MJPEG
- s. 640x480 MJPEG
- t. 320x240 MJPEG

F. Electrical:

~~1. Main supply input voltage:~~

~~a. 115VAC, 60Hz~~

2. Camera input voltage/power requirements: 24V AC, 60Hz, 12-15V DC, IEEE 802.3af PoE

3. Power Consumption: 15W(AC/DC) 12.3 W(PoE).

G. Mechanical:

1. Weight: 14.81 oz. (420~~430~~g).

2. Dimensions: 62.8 W x 64.2 H x 114.7 D mm (2.47" W x 2.53" H x 4.52" D)

H. Environmental:

1. Operating Temperature: 14°F to 122°F (-10° to +50°C) within 90% relative humidity.
2. Storage Temperature: -4°F to 158°F (-20°C to +70°C) within 70% maximum relative humidity.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine areas to receive devices and notify adverse conditions affecting installation or subsequent operation.
- B. Do not begin installation until unacceptable conditions are corrected.

3.2 PREPARATION

- A. Protect devices from damage during construction.

3.3 INSTALLATION

- A. Install devices in accordance with manufacturer's instruction at locations indicated on the floor drawings plans.
- B. Perform installation with qualified service personnel.
- C. Install devices in accordance with the National Electrical Code or applicable local codes.
- D. Ensure selected location is secure and offers protection from accidental damage.
- E. Location must provide reasonable temperature and humidity conditions, free from sources of electrical and electromagnetic interference.

3.4 FIELD QUALITY CONTROL

- A. Test snugness of mounting screws of all installed equipment.
- B. Test proper operation of all video system devices.
- C. Determine and report all problems to the manufacturer's customer service department.

3.5 ADJUSTING

- A. Make proper adjustment to video system devices for correct operation in accordance with manufacturer's instructions.
- B. Make any adjustment of camera settings to comply with specific customer's need.

3.6 DEMONSTRATION

- A. Demonstrate at final inspection that video management system used with devices functions properly.

END OF SECTION